TECHNICAL INFORMATION SHEET

QuickSeam™ Corner Flashing

Item Description
8.5" (216 mm) diameter

Item Number
W56RAC1644

Product Information

Description:

Firestone QuickSeam Corner Flashing consists of Firestone FormFlash™ factory laminated to QuickSeam Tape. It is designed to flash inside and outside corners of RubberGard™ EPDM roofing installations.

Method of Application:

1. Clean and prepare the RubberGard EPDM membrane using QuickPrime™ Plus, QuickPrime Plus LVOC, Single-Ply QuickPrime or Single-Ply LVOC Primer and a QuickScrubber™ or QuickScrubber Plus pad and handle to remove all dusting agents, dirt and other contaminants that will affect the finished seam.
2. When cloudy conditions below 60 °F (16 °C) occur, use heat guns (without ignition sources) to heat QuickSeam Corner Flashing. This will ensure good formability of the QuickSeam Corner Flashing to the primed substrate.
3. On sunny days less than 70 °F (21 °C), place QuickSeam Corner Flashing on roof (prior to application) with flashing side up to allow QuickSeam Corner Flashing to warm to ensure good formability.
4. On sunny days greater than 70 °F (21 °C), place QuickSeam Corner Flashing on roof (prior to application) with release paper side up to prevent QuickSeam Corner Flashing from gaining too much heat and to ensure good formability.
5. Refer to application instructions for specifics: www.firestonebpco.com

Storage:

- Store in original unopened containers indoors at temperatures between 60 °F (16 °C) and 80 °F (27 °C).
- Do not store on roof in direct sunlight or at temperatures above 80 °F (27 °C).
- When exposed to lower temperatures; restore to room temperature prior to use.

Shelf Life:

- Shelf life of one year can be expected when stored in original container at temperatures between 60 °F (16 °C) and 80 °F (27 °C).
- Shelf life will be shortened if exposed to elevated temperatures.

Precautions:

- Refer to Safety Data Sheet (SDS).
- FormFlash will cure when exposed to heat and over time.

LEED® Information:

Post-Consumer Recycled Content: 0%
Post Industrial Recycled Content: 0%
Manufacturing Location: Prescott, AR
*NOTE: LEED® is a registered trademark of the U.S. Green Building Council.

QuickSeam™ Corner Flashing

Packaging:

20 per carton, 100 cartons per pallet

NOTE: QuickScrubber and/or QuickScrubber Plus pads and handles are included in each carton. Quantities vary depending on the QuickSeam product.

Typical Properties

QUICKSEAM TAPE	
Property	**Test Method**
Base	Rubber Polymers
Color	Black
Solvents	None
Solids	100%
Cured State	Cured
Thickness	0.025" (0.64 mm) ± 0.005" (0.13 mm)

FLASHING MATERIAL	
Property	**Test Method**
Base	EPDM
Color	Black
Solvents	None
Solids	100%
Cured State	Uncured
Thickness	0.065" (1.59 mm) ± 0.005" (0.13 mm)
Size	8.5" (216 mm)

Please contact Firestone Technical Services Department at 1-800-428-4511 for further information.

This sheet is meant to highlight Firestone products and specifications and is subject to change without notice. Firestone takes responsibility for furnishing quality materials which meet published Firestone product specifications. Neither Firestone nor its representatives practice architecture. Firestone offers no opinion on and expressly disclaims any responsibility for the soundness of any structure. Firestone accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Firestone representative is authorized to vary this disclaimer.