

PRODUCT DATA SHEET

EVERBUILD® EpoxySET 105 Standard Cure

A THREE-PART GENERAL PURPOSE REPAIR MORTAR

PRODUCT DESCRIPTION

EVERBUILD® EpoxySET 105 Standard Cure is a three-part general purpose repair mortar based on epoxy resin technology. EVERBUILD® EpoxySET 105 Standard Cure is formulated to withstand chemicals, impact and abrasion and can be used to repair concrete, screeds, stone, brick and steel in even the most demanding domestic and industrial situations. EVERBUILD® EpoxySET 105 Standard Cure is the ideal product for repairing floors, steps, pipes, kerbs and sills. EVERBUILD® EpoxySET 105 Standard Cure is also the ideal choice for repairing cracks in masonry and concrete.

USES

For repairing:

- Heavy traffic areas
- Steps
- Walkways/Ramps
- Industrial floors

CHARACTERISTICS / ADVANTAGES

- Excellent chemical resistance
- Excellent impact and wear resistance.
- Can be laid in thin sections.
- Greater physical strength than conventional cementitious systems.
- Easy to mix.

PRODUCT INFORMATION

Packaging	4kg and 14kg Plastic tub
Colour	Grey
Shelf Life	24 months from date of manufacture.
Storage Conditions	Store in cool, dry conditions between 5°C and 25°C away from direct sunlight. Keep in original containers.
Density	2.03g/cm ³

TECHNICAL INFORMATION

Compressive Strength	50N/mm ² @24 hours (20°C)
Tensile Strength	15N/mm ² @ 7 days (20°C)
Tensile Adhesion Strength	Greater than the internal tensile strength of concrete
Abrasion Resistance	High
Service Temperature	-20°C to +50°C

APPLICATION INFORMATION

Consumption	4kg of mixed product will cover approximately 0.6m ² at 3mm depth. 14kg of mixed product will cover approximately 2.1m ² at 3mm depth.
Ambient Air Temperature	
Pot Life	The pot life of this product is 20-25 minutes at 20°C. Low temperatures will retard the cure. Do not apply below 4°C.
Curing Time	Initial: 24 hours. Final: 7 days. Do not traffic for 24 hours. If a faster cure is required, use EVERBUILD® EPOXY SET 106 (one hour cure)

APPLICATION INSTRUCTIONS

SUBSTRATE PREPARATION

Ensure surfaces are free from flaking material, dust, rust and grease. Saw/chisel edges to a defined area to a depth of 3mm. When applying to steel, shot blast, grind, or emery to a bright finish and remove residues.

APPLICATION METHOD / TOOLS

Before use, wear impervious gloves. Thoroughly mix components A and B with mixing stick and pour into suitable mixing vessel. Add the aggregate to this solution and mix thoroughly with a slow-speed drill and paddle. Trowel to desired finish with a clean steel trowel. Wipe the trowel intermittently with finishing solvent to reduce drag.

CLEANING OF TOOLS

Clean tools with finishing solvent.

LIMITATIONS

- Always mix as directed using all three components.
- Do not use where application would trap moisture within the substrate or in situations where hydrostatic pressure could break the bond.
- As the manufacturer cannot know all the uses their products may be put to, it is the user's responsibility to determine suitability for use. If in doubt, contact technical services department for advice.

VALUE BASE

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for the exact product data and uses.

ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

EVERBUILD BUILDING PRODUCTS LTD

Site 41, Knowsthorpe Way
Cross Green Industrial Estate
Leeds, LS9 0SW
Tel: 0113 240 3456
Web: www.everbuild.co.uk
Twitter: @everbuild

SIKA LIMITED

Watchmead
Welwyn Garden City
Hertfordshire, AL7 1BQ
Tel: 01707 394444
Web: www.sika.co.uk
Twitter: @SikaLimited

SIKA IRELAND LIMITED

Ballymun Industrial Estate
Ballymun
Dublin 11, Ireland
Tel: +353 1 862 0709
Web: www.sika.ie
Twitter: @SikaIreland

Product Data Sheet
EVERBUILD® EpoxySET 105 Standard Cure
June 2018, Version 01.01
020204030010000241



BUILDING TRUST



EVERBUILDEpoxySET105StandardCure-en-GBEVER-(06-2018)-1-1.pdf